



# **IPER**AUTOMATICA

## **Description**

Saeco created the connecting link between the OCS and Vending ranges: the new *IperAutomatica* table-top coffee machine

IperAutomatica has the new Heart of Coffee graphic design, developed by the designer Giuliano Galeazzi and that characterises the entire Vending range, with professional components that offer an innovative and versatile solution for small enterprises, offices and Ho.Re.Ca. applications (it can brew up to 8 different beverages, and is ideal for consumption rates of 30-50 products a day). With a height of 550 mm, it is perfect for kitchens; the water tank can be removed from three different directions: from above, from the left and from the right. It is easy to use and maintenance is also very quick, thanks to the modular internal elements.

## Accessories

- USB key kit
- Eva-Dts kit

#### **Main features**

- Professional components (brewing unit, coffee grinder, boiler)
- Modular internal elements (instant coffee module, coffee grinder module, brewing group module, water module), for ease of maintenance
- The lid can be lifted or taken off completely
- High dispensing area (145 mm)
- Customisable tags
- New powder dispensing system (new canisters, screw conveyor, nozzles, mixer)
- Advanced circuit board that makes it possible to customise recipes, be compatible with the main payment systems protocols (MDB, BDV, Executive - external box required) and to record statistical data through an EVA-DTS protocol
- Energy saving mode

#### User interface

- Keypad with 8 easy-to-read mechanical keys, covered by membrane, for direct access beverage selection
- I button for pre-selection
- Monochrome graphic display



# Technical data

## IperAutomatica Espresso

Structural specifications	
Dimensions ( $w \times h \times d$ )	346 × 547 × 542 mm
Weight	31,5 kg
Electrical specifications	
Power supply	220-240 V/50-60 Hz
Power pack	switching
Power consumption	1550₩
Water specifications	
Boiler	
Boiler capacity	300 cc − 1400 W
Boiler material	brass
Water supply	with independent water tank (with lock)
Other specifications	
Coffee beans canister	I I
Instant products canister	2
Number of selections	8
Pre-selection	I I
Mixer	I I
Brewing unit	7 gr
Capacities	
Water canister	41
Coffee grounds tray	25 coffee grounds
Drip tray	TI TI
Canisters capacity	
Coffee beans	1,0 kg
Milk	0,35 kg
Chocolate	0,90 kg

# **Technical specifications**

- Full welded and painted metal structure
- Containers and tanks in food-contact approved resin
- No water signal (capacitive water level sensor)
- Software function setting the maximum number of coffee cycles permitted before the dump box/drip tray is removed and emptied
- Electronically controlled boiler temperature
- Internal humidity exhaust and air flow grids
- 48 W electromagnetic vibration pump
- Boiler safety valve
- General safety relay for 24 V components
- CE, VDE approved

